

# SCYTHe



Tire Size	Rear Travel	Fork Travel	Head Angle	Seat Angle	BB Height
26x2.5"	7" (178mm) FR	7"	66.5	71.5	367mm (14.4")
26x2.5"	7" (178mm) DH	7"	66	71	361mm (14.2")
26x2.5"	7" (178mm) FR	8"	65.5	70.5	373mm (14.7")
26x2.5"	7" (178mm) DH	8"	65	70	368mm (14.5")
26x2.5"	8" (178mm) FR	7"	67.5	72.5	376mm (14.8")
26x2.5"	8" (178mm) DH	7"	67	72	370mm (14.6")
26x2.5"	8" (178mm) FR	8"	66.5	71.5	389mm (15.3")
26x2.5"	8" (178mm) DH	8"	66	71	384mm (15.1")

(as measured with 570mm axle-crown fork)

Size	S	M	L
<b>Seat tube</b>	390mm (15.3")	410mm (16.2")	442mm (17.5")
<b>Top Tube</b>	560mm (22")	573mm (22.6")	597mm (23.5")
<b>Wheel Base</b>	1119-1125mm (44-44.3")	1119-1125mm (44-44.3")	1119-1125mm (44-44.3")
<b>Head Angle</b>	65 - 66.5	65 - 66.5	66 - 66.5
<b>Seat Angle</b>	70 - 71.5	70 - 71.5	70 - 71.5
<b>BB Height</b>	363-391mm (14.3-15.4")	363-391mm (14.3-15.4")	363-391mm (14.3-15.4")
<b>Chainstay</b>	440-446mm (17.3-17.6")	440-446mm (17.3-17.6")	440-446mm (17.3-17.6")
<b>Head Tube length</b>	110mm (4.33")	120mm (4.725")	130mm (5.11")
<b>Max Tire Clearance</b>	26" x 2.8"	26" x 2.8"	26" x 2.8"
<b>Rear Hub Spacing</b>	150mm OLD	150mm OLD	150mm OLD
<b>Rear Dropout Axle Size</b>	12mm (maxle compatible)	12mm (maxle compatible)	12mm (maxle compatible)
<b>Head Tube</b>	1.5"	1.5"	1.5"
<b>Seatpost Dia</b>	30.0mm	30.0mm	30.0mm
<b>FD Clamp Dia</b>	34.9mm	34.9mm	34.9mm
<b>BB</b>	68mm - ISIS Drive   18mm	68mm - ISIS Drive   18mm	68mm - ISIS Drive   18mm
<b>Chainline</b>	50-51mm	50-51mm	50-51mm
<b>Chainguide</b>	ISCG 2005	ISCG 2005	ISCG 2005
<b>Shock</b>	8.75" x 2.75" [coil side 22.22mm x 8mm] [damper 40mm x 8mm]		
<b>Suggested Sag</b>	FR =20% - 30% // DH = 30%		

FOX		MANITOU	
RIDER WEIGHT lb (kg)	SPRING RATE	RIDER WEIGHT lb (kg)	SPRING RATE
<125 (60)	400	<125 (60)	300
125-150 (60-70)	450	125-150 (60-70)	350
150-175 (70-80)	500	150-175 (70-80)	400
175-200 (80-90)	550	175-200 (80-90)	450
200-225+ (90-100)	600	200-225+ (90-100)	500